




5V/3.3V 256Kx16 CMOS SRAM

SRAM

Features

- AS7C4098 (5V version)
- AS7C34098 (3.3V version)
- Industrial and commercial temperature
- Organization: 262,144 words \times 16 bits
- Center power and ground pins
- High speed
 - 10/12/15/20/25 ns address access time
 - 4/5/6/7 ns output enable access time
- Low power consumption: ACTIVE
 - 1375 mW (AS7C4098) / max @ 12 ns
 - 720 mW (AS7C34098) / max @ 12 ns

- Low power consumption: STANDBY
 - 55 mW (AS7C34098) / max CMOS
 - 36 mW (AS7C34098) / max CMOS
- Individual byte read/write controls
- 2.0V data retention
- Easy memory expansion with CE, OE inputs
- TTL- and CMOS-compatible, three-state I/O
- 44-pin JEDEC standard packages
 - 400 mil SOJ
 - 400 mil TSOP II
- ESD protection \geq 2000 volts
- Latch-up current \geq 200 mA

Logic block diagram**Pin arrangement**

44-pin SOJ, TSOP II (400 mil)

A0	1	○	44	A17
A1	2		43	A16
A2	3		42	A15
A3	4		41	OE
A4	5		40	UB
CE	6		39	LB
I/O0	7		38	I/O15
I/O1	8		37	I/O14
I/O2	9		36	I/O13
I/O3	10		35	I/O12
VCC	11		34	GND
GND	12		33	V _{CC}
I/O4	13		32	I/O1
I/O5	14		31	I/O10
I/O6	15		30	I/O9
I/O7	16		29	I/O8
WE	17		28	NC
A5	18		27	A14
A6	19		26	A13
A7	20		25	A12
A8	21		24	A11
A9	22		23	A10

Selection guide

	AS7C34098-10	AS7C4098-12 AS7C34098-12	AS7C4098-15 AS7C34098-15	AS7C4098-20 AS7C34098-20	AS7C4098-25 AS7C34098-25	Unit
Maximum address access time		10	12	15	20	ns
Maximum output enable access time		4	5	5	6	ns
Maximum operating current	AS7C4098	–	250	220	180	170S mA
AS7C34098	130	110	90	80	70	mA
Maximum CMOS standby current	AS7C4098	–	10	10	10	mA
AS7C34098	10	10	10	10	10	mA

Shaded areas indicate preliminary information.



Functional description

The AS7C4098 and AS7C34098 are high performance CMOS 4,194,304-bit Static Random Access Memory (SRAM) devices organized as 262,144 words × 16 bits. They are designed for memory applications where fast data access, low power, and simple interfacing are desired.

Equal address access and cycle times (t_{AA} , t_{RC} , t_{WC}) of 10/12/15/20/25 ns with output enable access times (t_{OE}) of 4/5/5/6/7 ns are ideal for high-performance applications. The chip enable input \overline{CE} permits easy memory expansion with multiple-bank memory systems.

When \overline{CE} is High the device enters standby mode. The standard AS7C4098 is guaranteed not to exceed 55 mW power consumption in CMOS standby mode. Both devices offer 2.0V data retention.

A write cycle is accomplished by asserting write enable (WE) and chip enable (\overline{CE}). Data on the input pins I/O0-I/O15 is written on the rising edge of WE (write cycle 1) or \overline{CE} (write cycle 2). To avoid bus contention, external devices should drive I/O pins only after outputs have been disabled with output enable (\overline{OE}) or write enable (WE).

A read cycle is accomplished by asserting output enable (\overline{OE}) and chip enable (\overline{CE}), with write enable (WE) High. The chip drives I/O pins with the data word referenced by the input address. When either chip enable or output enable is inactive, or write enable is active, output drivers stay in high-impedance mode.

These devices provide multiple center power and ground pins, and separate byte enable controls, allowing individual bytes to be written and read. \overline{LB} controls the lower bits, I/O0-I/O7, and \overline{UB} controls the higher bits, I/O8-I/O15.

All chip inputs and outputs are TTL- and CMOS-compatible, and operation is from either a single 5V (AS7C4098) or 3.3V (AS7C34098) supply. Both devices are available in the JEDEC standard 400-mL, 44-pin SOJ and TSOP II packages.

Absolute maximum ratings

Parameter	Device	Symbol	Min	Max	Unit
Voltage on V_{CC} relative to GND	AS7C4098	V_{t1}	-0.50	+7.0	V
	AS7C34098	V_{t1}	-0.50	+5.0	V
Voltage on any pin relative to GND		V_{t2}	-0.50	$V_{CC} + 0.50$	V
Power dissipation		P_D	-	1.5	W
Storage temperature (plastic)		T_{stg}	-65	+150	°C
Ambient temperature with V_{CC} applied		T_{bias}	-55	+125	°C
DC current into outputs (low)		I_{OUT}	-	+/- 20	mA

Stresses greater than those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions outside those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

Truth table

\overline{CE}	WE	\overline{OE}	\overline{LB}	\overline{UB}	I/O0-I/O7	I/O8-I/O15	Mode
H	X	X	X	X	High Z	High Z	Standby (I_{SB} , I_{SB1})
L	H	H	X	X	High Z	High Z	Output disable (I_{CC})
L	X	X	H	H			
L	H	L	L	H	D_{OUT}	High Z	Read (I_{CC})
			H	L	High Z	D_{OUT}	
			L	L	D_{OUT}	D_{OUT}	
L	L	X	L	H	D_{IN}	High Z	Write (I_{CC})
			H	L	High Z	D_{IN}	
			L	L	D_{IN}	D_{IN}	

Key: X = don't care, L = Low, H = High



Recommended operating conditions

Parameter		Symbol	Min	Typical	Max	Unit
Supply voltage	AS7C4098	V _{CC} (12/15/20/25)	4.5	5.0	5.5	V
	AS7C34098	V _{CC} (-10)	3.15	3.3	3.6	V
	AS7C34098	V _{CC} (12/15/20/25)	3.0	3.3	3.6	V
Input voltage	AS7C4098	V _{IH}	2.2	-	V _{CC} + 0.5	V
	AS7C34098	V _{IH}	2.0	-	V _{CC} + 0.5	V
		V _{IL}	-0.5 [†]	-	0.8	V
Ambient operating temperature	commercial	T _A	0	-	70	°C
	industrial	T _A	-40	-	85	°C

[†] V_{IL} min = -3.0V for pulse width less than t_{RC}/2.

DC operating characteristics (over the operating range)¹

Parameter	Sym	Test conditions	-10		-12		-15		-20		-25		Unit
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
Input leakage current	I _{LI}	V _{CC} = Max V _{IN} = GND to V _{CC}	-	1	-	1	-	1	-	1	-	1	µA
Output leakage current	I _{LO}	V _{CC} = Max CE = V _{IH} or OE = V _{IH} or WE = V _{IL} V _{I/O} = GND to V _{CC}	-	1	-	1	-	1	-	1	-	1	µA
Operating power supply current	I _{CC}	V _{CC} = Max Min cycle, 100% duty CE = V _{IL} , I _{OUT} = 0mA	AS7C4098	-	-	-	250	-	220	-	180	-	170 mA
			AS7C34098	-	130	-	110	-	90	-	80	-	70 mA
Standby power supply current	I _{SB}	V _{CC} = Max CE = V _{IH} , f=Max	AS7C4098	-	-	-	60	-	60	-	60	-	60 mA
			AS7C34098	-	60	-	60	-	60	-	60	-	60 mA
	I _{SB1}	V _{CC} = Max CE ≥ V _{CC} -0.2V, V _{IN} ≥ V _{CC} -0.2V or V _{IN} ≤ 0.2V, f=0	AS7C4098	-	-	-	10	-	10	-	10	-	10 mA
			AS7C34098	-	10	-	10	-	10	-	10	-	10 mA
Output voltage	V _{OL}	I _{OL} = 8 mA, V _{CC} = Min		-	0.4	-	0.4	-	0.4	-	0.4	-	0.4 V
	V _{OH}	I _{OH} = -4 mA, V _{CC} = Min		2.4	-	2.4	-	2.4	-	2.4	-	2.4	-

Shaded areas indicate preliminary information.

Capacitance (f = 1MHz, T_a = 25° C, V_{CC} = NOMINAL)²

Parameter	Symbol	Signals	Test conditions	Max	Unit
Input capacitance	C _{IN}	A, CE, WE, OE, UB, LB	V _{IN} = 0V	6	pF
I/O capacitance	C _{I/O}	I/O	V _{IN} = V _{OUT} = 0V	8	pF



Read cycle (over the operating range)^{3,9}


Parameter	Symbol	-10		-12		-15		-20		-25		Unit	Note
		Min	Max										
Read cycle time	t_{RC}	10	—	12	—	15	—	20	—	25	—	ns	
Address access time	t_{AA}	—	10	—	12	—	15	—	20	—	25	ns	
Chip enable (CE) access time	t_{ACE}	—	10	—	12	—	15	—	20	—	25	ns	
Output enable (OE) access time	t_{OE}	—	4	—	5	—	5	—	6	—	7	ns	
Output hold from address change	t_{OH}	3	—	3	—	3	—	3	—	3	—	ns	5
CE Low to output in low Z	t_{CLZ}	0	—	0	—	0	—	0	—	0	—	ns	4, 5
CE High to output in high Z	t_{CHZ}	—	3	—	3	—	4	—	5	—	6	ns	4, 5
OE Low to output in low Z	t_{OLZ}	0	—	0	—	0	—	0	—	0	—	ns	4, 5
OE High to output in high Z	t_{OHZ}	—	3	—	3	—	4	—	5	—	6	ns	4, 5
LB, UB access time	t_{BA}	—	4	—	5	—	5	—	6	—	7	ns	
LB, UB Low to output in low Z	t_{BLZ}	0	—	0	—	0	—	0	—	0	—	ns	
LB, UB High to output in high Z	t_{BHZ}	—	3	—	3	—	4	—	5	—	6	ns	
Power up time	t_{PU}	0	—	0	—	0	—	0	—	0	—	ns	5
Power down time	t_{PD}	—	10	—	12	—	15	—	20	—	25	ns	5

Shaded areas indicate preliminary information.


Key to switching waveforms

Rising input Falling input Undefined output/don't care

Read waveform 1 (address controlled)^{6,7,9}



Read waveform 2 (\overline{CE} , \overline{OE} , UB, LB controlled)^{6,8,9}






Write cycle (over the operating range)^{II}


Parameter	Symbol	-10		-12		-15		-20		-25		Unit	Note
		Min	Max										
Write cycle time	t_{WC}	10	–	12	–	15	–	20	–	25	–	ns	
Chip enable (\overline{CE}) to write end	t_{CW}	8	–	10	–	12	–	15	–	15	–	ns	
Address setup to write end	t_{AW}	8	–	10	–	12	–	15	–	15	–	ns	
Address setup time	t_{AS}	0	–	0	–	0	–	0	–	0	–	ns	
Write pulse width	t_{WP}	8	–	10	–	12	–	15	–	15	–	ns	
Address hold from end of write	t_{AH}	0	–	0	–	0	–	0	–	0	–	ns	
Data valid to write end	t_{DW}	5	–	6	–	7	–	10	–	12	–	ns	
Data hold time	t_{DH}	0	–	0	–	0	–	0	–	0	–	ns	4, 5
Write enable to output in High-Z	t_{WZ}	–	5	–	5	–	6	–	8	–	8	ns	4, 5
Output active from write end	t_{OW}	1	–	1	–	1	–	1	–	1	–	ns	4, 5
Byte enable Low to write end	t_{BW}	8	–	10	–	12	–	15	–	15	–	ns	4, 5

Shaded areas indicate preliminary information.

Write waveform 1 (\overline{WE} controlled)^{10,II}




Write waveform 2 (\overline{CE} controlled)^{10,II}






Write waveform 3^{10,11}



Data retention characteristics¹³

Parameter	Symbol	Test conditions	Min	Max	Unit
V _{CC} for data retention	V _{DR}	$V_{CC} = 2.0V$ $\overline{CE} \geq V_{CC} - 0.2V$ $V_{IN} \geq V_{CC} - 0.2V$ or $V_{IN} \leq 0.2V$	2.0	–	V
Data retention current	I _{CCDR}		–	500	μ A
Chip deselect to data retention time	t _{CDR}		0	–	ns
Operation recovery time	t _R		t _{RC}	–	ns
Input leakage current	I _{LI}		–	1	μ A

Data retention waveform





AC test conditions

- Output load: see Figure B or Figure C.
- Input pulse level: GND to 3.0V. See Figure A.
- Input rise and fall times: 2 ns. See Figure A.
- Input and output timing reference levels: 1.5V.




Figure A: Input pulse




Figure B: 5V Output load

Thevenin equivalent:
 $D_{out} \xrightarrow{168\Omega} +1.728V$ (5V and 3.3V)













Figure C: 3.3V Output load

Notes

- 1 During V_{CC} power-up, a pull-up resistor to V_{CC} on \overline{CE} is required to meet I_{SB} specification.
- 2 This parameter is sampled, but not 100% tested.
- 3 For test conditions, see AC Test Conditions, Figures A, B, C.
- 4 t_{CLZ} and t_{CHZ} are specified with $C_L = 5pF$ as in Figure C. Transition is measured $\pm 500mV$ from steady-state voltage.
- 5 This parameter is guaranteed, but not tested.
- 6 WE is High for read cycle.
- 7 CE and OE are Low for read cycle.
- 8 Address valid prior to or coincident with \overline{CE} transition Low.
- 9 All read cycle timings are referenced from the last valid address to the first transitioning address.
- 10 CE or WE must be High during address transitions. Either CE or WE asserting high terminates a write cycle.
- 11 All write cycle timings are referenced from the last valid address to the first transitioning address.
- 12 Not applicable.
- 13 2V data retention applies to commercial temperature range operation only.
- 14 $C=30pF$, except on High Z and Low Z parameters, where $C=5pF$.




Typical DC and AC characteristics¹²






Package dimensions



	44-pin TSOP II	
	Min (mm)	Max (mm)
A		1.2
A ₁	0.05	
A ₂	0.95	1.05
b	0.25	0.45
c	0.15 (typical)	
d	20.85	21.05
e	10.06	10.26
H _e	11.56	11.96
E	0.80 (typical)	
l	0.40	0.60



	44-pin SOJ 400 mil	
	Min	Max
A	0.128	0.148
A ₁	0.025	-
A ₂	1.105	1.115
B	0.026	0.032
b	0.015	0.020
c	0.007	0.013
D	1.120	1.130
E	0.370 NOM	
E ₁	0.395	0.405
E ₂	0.435	0.445
e	0.050 NOM	

Ordering codes

Package	Version	10 ns	12 ns	15 ns	20 ns	25 ns
SOJ	5V commercial	NA	AS7C4098-12JC	AS7C4098-15JC	AS7C4098-20JC	AS7C4098-25JC
	5V industrial	NA	AS7C4098-12JI	AS7C4098-15JI	AS7C4098-20JI	AS7C4098-25JI
	3.3V commercial	AS7C34098-10JC	AS7C34098-12JC	AS7C34098-15JC	AS7C34098-20JC	AS7C34098-25JC
	3.3V industrial	NA	AS7C34098-12JI	AS7C34098-15JI	AS7C34098-20JI	AS7C34098-25JI
TSOP II	5V commercial	NA	AS7C4098-12TC	AS7C4098-15TC	AS7C4098-20TC	AS7C4098-25TC
	5V industrial	NA	AS7C4098-12TI	AS7C4098-15TI	AS7C4098-20TI	AS7C4098-25TI
	3.3V commercial	AS7C34098-10TC	AS7C34098-12TC	AS7C34098-15TC	AS7C34098-20TC	AS7C34098-25TC
	3.3V industrial	NA	AS7C34098-12TI	AS7C34098-15TI	AS7C34098-20TI	AS7C34098-25TI

NA: not available.

Part numbering system

AS7C	X	4098	-XX	X	X
SRAM prefix	Blank=5V CMOS 3=3.3V CMOS	Device number	Access time	Package: J=SOJ 400 mil T=TSOP II 400 mil	Temperature range, C=Commercial: 0°C to 70°C I=Industrial: -40°C to 85°C

AS7C4098
AS7C34098



SRAM